

2 doors Horizontal Refrigerators

GN 1/1

NT 0/+10°C



Main features:

Inside and outside made of Stainless Steel, except for the external bottom made of Galvanized Steel. Internal rounded corners. High Pressure Polyurethane injected without hazardous gases for the environment. Insulation thickness NT counters: 40 mm. Insulation thickness LT counters: 60 mm. Self-closing doors with magnetic gaskets. Electronic front control panel with NTC probe. Ventilated cooling. Tropicalized and extractable "monoblock type" condensing unit (ambient temperature +43°C and relative humidity of 65%) with gas R404A/R507. Refrigerated NT and LT counters designed also for remote condensing unit. Completely automatic defrosting and condense water evaporation. Adjustable Stainless Steel feet (110/190 H mm). Personalization options available.



Standard set up:

- 2 GN 1/1 Rilsan shelf
- 4 Stainless Steel "L" runners
- Set of 2 castors w th brake and 2 w thout brake



Stainless Steel AISI 304

DIMENSIONS	WxDxH mm	1420x700x850/920
NET WEIGHT	kg	86
NET CAPACITY	l	310
TEMPERATURE	°C	0 / +10
GAS	GAS	R404A/R507
TEST DETAILS	°C / RH	+43 / 65%
ABSORBED POWER	W	495
ENERGY CONSUMPTION	kWh/year	1182,56
POWER SUPPLY	V-P-Hz	230-1-50



Mobile: 0414 887 298
Phone: 07 3279 5204
Fax: 07 3376 4142
paul@acecateringequipment.com.au
www.acecateringequipment.com.au

100% Made in Italy